

SM8SvvA/CA



TRANSIENT VOLTAGE SUPPRESSOR DIODES

V_{RWM}: 10~85 Volts

P_{PP}: 6600 W

Package: DO-218AB

Features


- NH'S Glass Passivated Chip Technology
- Wave And Reflow Solderable
- Low Reverse Leakage
- Very Fast Response Time
- Excellent Clamping Capability
- 10/1000μs Waveform, Repetition Rate(Duty Cycle):0.01 %
- ESD Immunity Acc. IEC 61000-4-2

Typical Applications


- Power Port
- Communication And Data Port
- ESD Protection And Automotive Electronics
- Industrial Control and Automation

Diagram:

UNI




BI




Polarity:

UNI



BI



Maximum Ratings (Ta=25°C Unless Otherwise Specified)

Parameter	Test Conditions	Symbol	Value	Unit
Non-Repetitive Peak Pulse Power Dissipation	10/1000μs Waveform	P_{PP}	6600	W
Peak Pulse Current	10/1000μs Waveform	I_{PP}	See Table-1	A
Peak Forward Surge Current (Only UNI)	8.3ms Single Half Sine-Wave Superimposed On Rate Load	I_{FSM}	700	A
Power Dissipation On Infinite Heatsink	T _L = 25.0 °C	P_D	8.0	W

Thermal Characteristics (Ta=25°C Unless Otherwise Specified)

Parameter	Test Conditions	Symbol	Value	Unit
Operating Junction Temperature Range		T_J	-55 ~ 175	°C
Storage Temperature Range		T_{STG}	-55 ~ 175	
Thermal Resistance Junction To Ambient With Steady-State	Device Mounted On 1 in2 FR-4 Board With 2oz. Copper	R_{θJA}	55	°C/W

C-V Curve Chart

Symbol Instruction

UNI	BI	Symbol	Instruction
		I_{PP}	Maximum Reverse Peak Pulse Current
		V_C	Clamping Voltage @ I _{PP}
		P_{PP}	Peak Power Dissipation
		V_{RWM}	Working Peak Reverse Voltage
		I_R	Maximum Reverse Leakage Current @ V _{RWM}
		V_{BR}	Breakdown Reverse Voltage
		I_T	Test Current @ V _{RWM}
		I_F	Maximum Average Forward Rectified Current
		V_F	Maximum Instantaneous Forward Voltage
		C_J	Junction Capacitance @ VR = 0 and f = 1.0 MHz

SM8SvvA/CA

TRANSIENT VOLTAGE SUPPRESSOR DIODES
Table-1.ELECTRICAL CHARACTERISTICS (Ta=25°C unless otherwise noted)

Part Number And Code		Reverse Stand-off Voltage	Breakdown Voltage VBR @ I _T		Test Current	Max. Clamping Voltage @ I _{PP}	Max. Peak Pulse Current	Max. Reverse Leakage @ V _{RWM}
UNI-POLAR	BI-POLAR	V _{RWM} (V)	Min.(V)	Max.(V)	I _T (mA)	V _{C Max} (V)	IPP(A)	I _R (uA)
SM8S10A	SM8S10CA	10	11.1	12.3	5	17.0	388.2	10
SM8S11A	SM8S11CA	11	12.2	13.5	5	18.2	362.6	10
SM8S12A	SM8S12CA	12	13.3	14.7	5	19.9	331.7	10
SM8S13A	SM8S13CA	13	14.4	15.9	5	21.5	307.0	5
SM8S14A	SM8S14CA	14	15.6	17.2	5	23.2	284.5	5
SM8S15A	SM8S15CA	15	16.7	18.5	5	24.4	270.5	5
SM8S16A	SM8S16CA	16	17.8	19.7	5	26.0	253.8	5
SM8S17A	SM8S17CA	17	18.9	20.9	5	27.6	239.1	5
SM8S18A	SM8S18CA	18	20.0	22.1	5	29.2	226.0	5
SM8S20A	SM8S20CA	20	22.2	24.5	5	32.4	203.7	5
SM8S22A	SM8S22CA	22	24.4	26.9	5	35.5	185.9	5
SM8S24A	SM8S24CA	24	26.7	29.5	5	38.9	169.7	5
SM8S26A	SM8S26CA	26	28.9	31.9	5	42.1	156.8	5
SM8S28A	SM8S28CA	28	31.1	34.4	5	45.4	145.4	5
SM8S30A	SM8S30CA	30	33.3	36.8	5	48.4	136.4	5
SM8S33A	SM8S33CA	33	36.7	40.6	5	53.3	123.8	5
SM8S36A	SM8S36CA	36	40.0	44.2	5	58.1	113.6	5
SM8S40A	SM8S40CA	40	44.4	49.1	5	64.5	102.3	5
SM8S43A	SM8S43CA	43	47.8	52.8	5	69.4	95.1	5
SM8S45A	SM8S45CA	45	50.0	55.3	5	72.7	90.8	5
SM8S48A	SM8S48CA	48	53.3	58.9	5	77.4	85.3	5
SM8S51A	SM8S51CA	51	56.7	62.7	5	82.4	80.1	5
SM8S54A	SM8S54CA	54	60.0	66.3	5	87.1	75.8	5
SM8S58A	SM8S58CA	58	64.4	71.2	5	93.6	70.5	5
SM8S60A	SM8S60CA	60	66.7	73.7	5	96.8	68.2	5
SM8S64A	SM8S64CA	64	71.1	78.6	5	103.0	64.1	5
SM8S70A	SM8S70CA	70	77.80	86.00	5	113.0	58.4	5
SM8S75A	SM8S75CA	75	83.30	92.10	5	121.0	54.5	5
SM8S78A	SM8S78CA	78	86.70	95.80	5	126.0	52.4	5
SM8S85A	SM8S85CA	85	94.40	104.00	5	137.0	48.2	5

SM8SvvA/CA

TRANSIENT VOLTAGE SUPPRESSOR DIODES



Typical Characteristics Curves




Fig.1-Peak Power Or Current Vs.Tc




Fig.2-Steady State Power Derating Curve




Fig.3-Peak Pulse Power Rating Curve




Fig.4-Typical Junction Capacitance




Fig.5-Max. Non-Repetitive Surge Current





Fig.6-Pulse Waveform

SM8SvvA/CA

TRANSIENT VOLTAGE SUPPRESSOR DIODES




OUTLINE DRAWINGS



DO-218AB

OUTLINE DIMENSIONS						
Dim.	Milimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	14.80	-	16.20	0.5827	-	0.6378
B	13.00	-	14.00	0.5118	-	0.5512
C	8.70	-	9.30	0.3425	-	0.3661
D	9.60	-	10.40	0.3780	-	0.4094
E	8.20	-	8.80	0.3228	-	0.3465
F	2.20	-	2.80	0.0866	-	0.1102
G	4.55	-	5.15	0.1791	-	0.2028
H	0.50	-	0.70	0.0197	-	0.0276

RECOMMEDND LAYOUT DRAWINGS




DO-218AB

OUTLINE DIMENSIONS						
Dim.	Milimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	-	10.00	-	-	0.3937	-
B	-	9.00	-	-	0.3543	-
C	-	2.50	-	-	0.0984	-
D	-	3.60	-	-	0.1417	-

SM8SvvA/CA



TRANSIENT VOLTAGE SUPPRESSOR DIODES

MARKING(UNI)		MARKING INSTRUCTION				
		NH=Niuhan Trademark FF=Product Line Code,According To Actual Changes YWW=Date Code,According To Actual Changes LLWWF=Inernal Code,According To Actual Changes SM8SvvA=Model,vv=See Table-1				
MARKING(BI)		MARKING INSTRUCTION				
		NH=Niuhan Trademark FF=Product Line Code,According To Actual Changes YWW=Date Code,According To Actual Changes LLWWF=Inernal Code,According To Actual Changes SM8SvvCA=Model,vv=See Table-1				
PACKING INFORMATION						
Package Type	Package Code	Product Weight Approx(g/Pcs)	Package Method	Quantity (Pcs/Min. Pack.)	Quantity (Pcs/Inner Box)	Quantity (Pcs/Carton)
DO-218AB	P1	3.046	13" Reel	750	750	6000

SM8SvvA/CA


TRANSIENT VOLTAGE SUPPRESSOR DIODES



Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds

Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T _{smax} to T _p)	3°C/second max.	3°C/second max.
Preheat -Temperature Min(TS min) -Temperature Max(TS max) -Time(ts min to ts max)	100°C 150°C 60-120 seconds	150°C 200°C 60-180 seconds
Time maintained above: -Temperature (TL) - Time (tL)	183°C 60-150 seconds	217°C 60-150 seconds
Peak Temperature(TP)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

SM8SvvA/CA



TRANSIENT VOLTAGE SUPPRESSOR DIODES

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Niuhang Electronics Technology Co., LTD
- Niuhang Electronics Technology Co., LTD. reserves the rights to make changes of the content herein the document anytime without notification.
- Niuhang Electronics Technology Co., LTD. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Niuhang Electronics Technology Co., LTD. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Niuhang Electronics Technology Co., LTD. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Niuhang Electronics Technology Co., LTD. for any damages resulting from such improper use or sale.
- When the appearance of the product and chip size does not change, in order to produce the customer's quality, change the internal structure and the production process Niuhang can not notify