

NCD20A65PT

Silicon Carbide Schottky Diode

Voltage: 650 Volts

Current: 20 A

Package: TO-247

Features

- NH'S Advanced Silicon Carbide Schottky Technology
- Zero Reverse Recovery
- Positive Temperature Coefficient On VF
- Extremely Fast Switching And Extremely Low Leakage Current


Mechanical Data

- **Case:** Molded With UL-94 ClassV-0 Recognized, RoHS-Compliant
- **Polarity:** Look At The Diagram And Polarity On The Right
- **Terminals:** Tin Plated Leads,Solderable Per J-STD-002 And JESD22-B102


Typical Applications

- Power Factor Correction (PFC)
- Interruptible Power Supply (UPS)
- Switch Mode Power Supply (SMPS)

Diagram:



Polarity:



Maximum Ratings (Ta=25°C Unless Otherwise Specified)

Parameter	Test Conditions	Symbol	Ratings	Unit
Maximum Repetitive Peak Reverse Voltage		V_{RRM}	650	V
Maximum DC Blocking Voltage		V_{DC}	650	V
Max Average Forward Rectified Current	$T_C = 25^\circ\text{C}$ $T_C = 110^\circ\text{C}$ $T_C = 150^\circ\text{C}$	$I_{F(AV)}$	54 34 20	A
Peak Forward Surge Current Per Diode Sine Half-Wave	$T_C = 25^\circ\text{C}, T_P = 10\text{ms}$ $T_C = 110^\circ\text{C}, T_P = 10\text{ms}$	I_{FSM}	75 66	A
Peak Forward Surge Current Per Diode Sine Half-Wave	$T_C = 25^\circ\text{C}, T_P = 10\text{ms}$ $T_C = 110^\circ\text{C}, T_P = 10\text{ms}$	I_{FRM}	69 61	A
Maximum Power Dissipation Power	$T_C = 25^\circ\text{C}$	P_{tot}	83	W
Dissipation Derating Factor Above 25°C	$T_C = 100^\circ\text{C}$		42	
Current Squared Time Per Diode	$t < 8.3\text{ms}$	I^2t	23.3	A ² sec
Avalanche Current, Single Pulse (Note 1)	$L = 0.5\text{ mH}$	I_{AS}	7.5	A
Single Pulse Avalanche Energy (Note 1)	$L = 0.5\text{ mH}, I_{PK} = 7.5\text{ A}$	E_{AS}	14	mJ
Test Circuit & Waveform See Fig.16	Starting $T_J = 25^\circ\text{C}, V_{DD} = 50.0\text{ V}$			

Electrical Characteristics (Ta=25°C Unless Otherwise Specified)

Parameter	Test Conditions	Symbol	Ratings			Unit
			Min.	Typ.	Max.	
Instantaneous Forward Voltage Per Diode	$T_a = 25^\circ\text{C}$ $T_a = 175^\circ\text{C}$ $I_F = 10.0\text{ A}$	V_F	--	1.36 1.66	1.65 --	V
Maximum DC Reverse Current at Rated DC Blocking Voltage	$T_a = 25^\circ\text{C}$ $V_R = V_{RRM}$ $T_a = 175^\circ\text{C}$ $V_R = 80\% \cdot V_{RRM}$	I_{RRM}	--	1.0 8.5	40.0 --	uA
Capacitance stored energy	$V_R = 400.0\text{ V}$	E_C	--	4.2	--	uJ
Total Capacitive Charge	$Q_C = \int_0^{V_R} C \cdot dV$ $V_R = 400.0\text{ V}$	Q_C	--	29	-	nC
Typical Junction Capacitance Per Diode	1 V, 1MHz	C_J	--	390	--	pF
	200 V, 1MHz		--	56	--	
	400 V, 1MHz		--	40	--	

Thermal Characteristics (Ta=25°C Unless Otherwise Specified)

Parameter	Test Conditions	Symbol	Ratings	Unit
Operating Junction Temperature Range		T_J	-55 to 175	°C
Storage Temperature Range		T_{STD}	-55 to 175	
Max Thermal Resistance Junction-Case With Steady-State	Device Mounted On 75mm x 45mm x 2.5mm Alu. Heat.	$R_{\theta JC}$	1.80	°C/W

NCD20A65PT

Silicon Carbide Schottky Diode



Typical Characteristics Curves




Fig.1-Forward Current Derating Curve




Fig.2-Typical Instantaneous Forward




Fig.3-Typical Reverse Characteristics




Fig.4-Typical Junction Capacitance




Fig.5-Max. Non-Repetitive Surge Current




Fig.6-Total Capacitance Charge Characteristics vs. Reverse Voltage

NCD20A65PT

Silicon Carbide Schottky Diode



Typical Characteristics Curves




Fig.7-Power dissipation as function of case temperature




Fig.8-Capacitance Stored Energy





Fig.9- Normalized Maximum Transient Thermal Impedance Vs.Pulse Width

NCD20A65PT

Silicon Carbide Schottky Diode




OUTLINE DRAWINGS



TO-247

OUTLINE DIMENSIONS						
Dim.	Milimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	15.25	-	16.75	0.6004	-	0.6594
B	20.50	-	22.50	0.8071	-	0.8858
C	4.50	-	5.10	0.1772	-	0.2008
D	0.40	-	0.80	0.0157	-	0.0315
E	3.40	-	4.00	0.1339	-	0.1575
F	1.80	-	2.20	0.0709	-	0.0866
G	2.70	-	3.30	0.1063	-	0.1299
H	1.00	-	1.40	0.0394	-	0.0551
J	5.15	-	5.75	0.2028	-	0.2264
L	18.50	-	20.50	0.7283	-	0.8071
O	2.85	-	3.15	0.1122	-	0.1240

RECOMMEDND LAYOUT DRAWINGS



TO-247


OUTLINE DIMENSIONS						
Dim.	Milimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	-	2.00	-	-	0.0787	-
B	-	2.00	-	-	0.0787	-
C	-	5.50	-	-	0.2165	-
D	-	1.40	-	-	0.0551	-

NCD20A65PT

Silicon Carbide Schottky Diode



MARKING



MARKING INSTRUCTION

NH=Niuhang Trademark
FF=Product Line Code,According To Actual Changes
YWW=Date Code,According To Actual Changes
LLWWF=Inernal Code,According To Actual Changes
NCD20A65PT=Model

PACKING INFORMATION

Package Type	Package Code	Product Weight Approx(g/Pcs)	Package Method	Quantity (Pcs/Min. Pack.)	Quantity (Pcs/Inner Box)	Quantity (Pcs/Carton)
TO-247	P1	5.778	Tube	30	600	2400

NCD20A65PT

Silicon Carbide Schottky Diode



Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds

Recommended temperature profile for IR reflow

	Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
	Average ramp-up rate (T _s max to T _p)	3°C/second max.	3°C/second max.
	Preheat-Temperature Min (T _S min) -Temperature Max (T _S max) -Time(t _s min to t _s max)	100°C 150°C 60-120 seconds	150°C 200°C 60-180 seconds
	Time maintained above: -Temperature (T _L) - Time (t _L)	183°C 60-150 seconds	217°C 60-150 seconds
	Peak Temperature(T _P)	240 +0/-5 °C	260 +0/-5 °C
	Time within 5°C of actual peak temperature (t _p)	10-30 seconds	20-40 seconds
	Ramp down rate	6°C/second max.	6°C/second max.
	Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Niuhan Electronics Technology Co., LTD
- Niuhan Electronics Technology Co., LTD. reserves the rights to make changes of the content herein the document anytime without notification.
- Niuhan Electronics Technology Co., LTD. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Niuhan Electronics Technology Co., LTD. does not assume any and all implied warranties,including warranties of fitness for particular purpose,non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation.Customers are responsible in comprehending the suitable use in particular applications.Niuhan Electronics Technology Co., LTD.makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining,such as medical instruments,transportation equipment,aerospae machinery et cetera.Customers usin or selling these products for use in such applications do so at their own risk and agree to fully indemnify Niuhan Electronics Technology Co., LTD.for any damages resulting resulting from such improper use or sale.
- When the appearance of the product and chip size does not change, in order to product the customer. quality, change the internal structure and the production process Niuhan can not notify

NCD20A65PT

Silicon Carbide Schottky Diode



Specification Revision History

Rev.	Date	Changed Items	Pre-Changed Content	Changed Content
A/1	2014-10-20	First Issue		
Blank Below				