

NGT15N65D



N-Channel Enhancement Type IGBT With FRD

Voltage: 650 Volts

Current: 15 Ampers

Package: TO-263

Features

- NH'S Advanced IGBT Technology
- Low Vcesat For Low On-State Loss
- Very Soft Ultra-Fast Recovery Antiparallel Diode
- High Frequency Operation For High Reliability


Typical Applications

- Power Factor Correction(PFC)
- Motor Drives
- Uninterruptible Power Supplies(UPS)
- High Frequency Inverters


Product Summary

V _{CES} Min.@T _j	650	V
I _C Min.@100℃	15	A
V _{CE(sat)} @25℃	1.5	V

Diagram:



Polarity:



Absolute Maximum Ratings (Ta=25℃ Unless Otherwise Specified)

Parameter	Test Conditions	Symbol	Ratings	Unit
Collector-Emitter Voltage (V _{GS} =0)		V _{CES}	650	V
Gate-Emitter Voltage		V _{GES}	±30	V
Continuous Collector Current (Note 1)	Ta= 25 ℃	I _C	30	A
	Ta= 100 ℃		15	
Drain Current-Pulse (Note 1)	T _j < 175 ℃	I _{CM}	60	A
Maximum Power Dissipation Power	Ta= 25 ℃	P _D	300	W
Dissipation Derating Factor Above 25℃	Ta= 100 ℃		150	
Derating Factor		D _F	2.00	W/℃

Thermal Characteristics (Ta=25℃ Unless Otherwise Specified)

Parameter	Test Conditions	Symbol	Typ.	Unit
Junction Temperature		T _J	-50 to 175	℃
Storage Temperature Range		T _{STD}	-50 to 175	℃
Thermal Resistance Junction To Ambient With Steady-State	Still Air Environment With Ta=25℃	R _{θJA}	62	℃/W
Thermal Resistance Junction-Case(IGBT) With Steady-State	Device Mounted On 1 in2 FR-4 Board With 2oz. Copper	R _{θJC}	0.5	
Thermal Resistance Junction-Case(FRD) With Steady-State	Device Mounted On 1 in2 FR-4 Board With 2oz. Copper	R _{θJC}	1.6	

Notes: 1.Pulse Width Limited By Max. Junction Temperature. (See Fig. 20).

NGT15N65D

N-Channel Enhancement Type IGBT With FRD
Electrical Characteristics (Ta=25°C Unless Otherwise Specified)

Parameter	Test Conditions	Symbol	Min.	Typ.	Max.	Unit
Static Off Characteristics						
Collector To Emitter Voltage	VGE=0V, IC=1mA	BV _{CES}	650	--	--	V
Collector To Emitter Leakage Current	VCE= 650 V, VGE=0V, Tj=25℃	I _{CES}	--	--	0.5	uA
	VCE= 520 V, VGE=0V, Tj=125℃		--	0.5	2	mA
Gate To Emitter Leakage Current	VGE= 20 V, VCE=0V	I _{GES}	--	--	250	nA
Emitter To Gate Leakage Current	VGE= -20 V, VCE=0V	I _{EGS}	--	--	250	nA
Forward Transconductance	IC= 7.5 A, VCE= 15 V	gfs	--	5.9	--	S
Static On Characteristics						
Gate Threshold Voltage	VGE= VCE, IC=250uA	V _{GE(TH)}	4.5	5.3	6	V
Collector-Emitter Saturation Voltage	IC= 7.5 A, VGE= 15.0 V, Tj=25℃	V _{CE(SAT)}	--	1.50	2.00	V
	IC= 7.5 A, VGE= 15.0 V, Tj=125℃		--	1.8	--	
Dynamic Characteristics						
Input Capacitance	VCE= 25 V	C _{ies}	--	1123	--	pF
Output Capacitance	VGE= 0 V	C _{oes}	--	44	--	pF
Reverse Transfer Capacitance	F= 1 MHZ	C _{res}	--	4	--	pF
Switching Paramters (Test Circuit & Waveform See Fig.21)						
Turn-On Delay Time	VCE= 312 V IC= 8 A	Tj=25℃	t _{d(on)}	--	8	ns
		Tj=175℃		--	9	
Turn-On Rise Time	VGE= 15.0 V RG= 10 Ω	Tj=25℃	t _r	--	24	ns
		Tj=175℃		--	26	
Turn-Off Delay Time		Tj=25℃	t _{d(off)}	--	66	ns
		Tj=175℃		--	86	
Turn-Off Rise Time		Tj=25℃	t _f	--	76	ns
		Tj=175℃		--	95	
Turn-On Switching Loss	Inductive Load	Tj=25℃	E _{on}	--	28	μJ
Tj=175℃		--		31	--	
Turn-Off Switching Loss		Tj=25℃	E _{off}	--	89	μJ
Tj=175℃		--		111	--	
Total Switching Energy		Tj=25℃	E _{tot}	--	117	μJ
		Tj=175℃		--	142	
Gate Charge Paramters (Test Circuit & Waveform See Fig.22)						
Total Gate Charge	VCE= 312 V	Q _g	--	41	--	nC
Gate-Emitter Charge	VGE= 15 V	Q _{ge}	--	12	--	nC
Gate-Collector Charge	IC= 7.5 A	Q _{gc}	--	15	--	nC

NGT15N65D



N-Channel Enhancement Type IGBT With FRD

Electrical Characteristics (Ta=25°C Unless Otherwise Specified)

Parameter	Test Conditions		Symbol	Min.	Typ.	Max.	Unit
Collector-Emitter Diode Characteristics And Maximum Ratings (Test Circuit & Waveform See Fig.24)							
Max. Diode Forward Cuurent	Tj= 25 °C		I _F	--	--	30.0	A
tp Limited by Tj(max)	Tj= 100 °C			--	--	15.0	
Max. Pulsed Forward Cuurent			I _{SM}	--	--	60	A
Diode Forward Voltage	IF= 15.0 A,VGE=-0V		V _F	--	1.60	2.10	V
Reverse Recovery Time	IF= 7.5 A di/dt= 200 A/us	Tj=25°C	t _{rr}	--	45	--	ns
		Tj=175°C		--	90.0	--	
Reverse Recovery Charge	VGE= 0.0 V VCE= 40 V	Tj=25°C	Q _{rr}	--	142	--	nC
		Tj=175°C		--	475.7	--	
Reverse Recovery Current		Tj=25°C	I _{rrm}	--	6.0	--	A
		Tj=175°C		--	10.6	--	
Reverse Recovery Energy		Tj=25°C	E _{rr}	--	5.4	--	μJ
		Tj=175°C		--	19.1	--	

NGT15N65D



N-Channel Enhancement Type IGBT With FRD

Typical Characteristics Curves




Fig.1-Output Characteristics@ $T_j=25^\circ\text{C}$




Fig.2-Output Characteristics@ $T_j=175^\circ\text{C}$




Fig.3-Transfer Characteristics




Fig.4-Gate Emitter Threshold Voltage Vs. Junction Temperature




Fig.5-Saturation Voltage vs. Junction Temperature




Fig.6-Saturation Voltage vs. Collector-To-Emitter Current

NGT15N65D



N-Channel Enhancement Type IGBT With FRD

Typical Characteristics Curves




Fig.7-Typical Switching Times Vs. Junction Temperature




Fig.8-Typical Switching Times Vs. External Gate Resistance




Fig.9-Typical Switching Energy Vs. Junction Temperature




Fig.10-Typical Switching Energy Vs. External Gate Resistance




Fig.11-Typical Switching Energy Vs. Collector-To-Emitter Current




Fig.12-Typical Switching Energy Vs. Collector-To-Emitter Voltage

NGT15N65D



N-Channel Enhancement Type IGBT With FRD

Typical Characteristics Curves




Fig.13-Maximum Continuous Collector Current Vs. Case Temperature




Fig.14-Maximum Power Dissipation Vs. Case Temperature




Fig.15-Emitter-To-Collector Diode Forward Voltage




Fig.16-Breakdown Voltage Vs. Junction Temperature




Fig.17-Gate Charge Waveform






Fig.18-Typical Capacitance Vs. Collector-To-Emitter Voltage

NGT15N65D




N-Channel Enhancement Type IGBT With FRD

Typical Characteristics Curves



Test Circuit & Waveform



NGT15N65D



N-Channel Enhancement Type IGBT With FRD

Test Circuit & Waveform




Fig.22- Gate Charge Test Circuit & Waveform




Fig.23- Unclamped Inductive Switching (UIS) Test Circuit & Waveform




Fig.24- Diode Recovery Test Circuit & Waveform


NGT15N65D

N-Channel Enhancement Type IGBT With FRD



OUTLINE DRAWINGS


TO-263



OUTLINE DIMENSIONS						
Dim.	Milimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	9.30	-	10.50	0.3661	-	0.4134
B	9.60	-	11.60	0.3780	-	0.4567
C	8.20	-	9.50	0.3228	-	0.3740
D	4.00	-	5.00	0.1575	-	0.1969
E	1.00	-	1.70	0.0394	-	0.0669
F	0.20	-	0.70	0.0079	-	0.0276
G	4.45	-	5.25	0.1752	-	0.2067
H	1.25	-	1.85	0.0492	-	0.0728
J	1.00	-	1.60	0.0394	-	0.0630
K	0.60	-	1.00	0.0236	-	0.0394
L	2.25	-	2.80	0.0886	-	0.1102

RECOMMEDND LAYOUT DRAWINGS

TO-263




OUTLINE DIMENSIONS						
Dim.	Milimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	-	10.86	-	-	0.4276	-
B	-	7.86	-	-	0.3094	-
C	-	11.64	-	-	0.4583	-
D	-	5.08	-	-	0.2000	-
E	-	3.62	-	-	0.1425	-
F	-	1.14	-	-	0.0449	-

NGT15N65D

N-Channel Enhancement Type IGBT With FRD



MARKING INFORMATION



MARKING INSTRUCTIONS

NH=Niuhang Trademark
FF=Product Line Code,According To Actual Changes
YWW=Date Code,According To Actual Changes
LLWWF=Inernal Code,According To Actual Changes
NGT15N65D=Model

PACKING INFORMATION

Package Type	Package Code	Product Weight Approx(g/Pcs)	Package Method	Quantity (Pcs/Min. Pack.)	Quantity (Pcs/Inner Box)	Quantity (Pcs/Carton)
TO-263	P1	1.4331	13" Reel	800	800	4000
TO-263	P2	1.4331	13" Reel	800	800	4800

NGT15N65D



N-Channel Enhancement Type IGBT With FRD

Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds

Recommended temperature profile for IR reflow

	Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
	Average ramp-up rate (T _{smax} to T _p)	3°C/second max.	3°C/second max.
	Preheat-Temperature Min (T _S min) -Temperature Max (T _S max) -Time(t _s min to t _s max)	100°C 150°C 60-120 seconds	150°C 200°C 60-180 seconds
	Time maintained above: -Temperature (T _L) - Time (t _L)	183°C 60-150 seconds	217°C 60-150 seconds
	Peak Temperature(T _P)	240 +0/-5 °C	260 +0/-5 °C
	Time within 5°C of actual peak temperature (t _p)	10-30 seconds	20-40 seconds
	Ramp down rate	6°C/second max.	6°C/second max.
	Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Niuhang Electronics Technology Co., LTD
- Niuhang Electronics Technology Co., LTD. reserves the rights to make changes of the content herein the document anytime without notification.
- Niuhang Electronics Technology Co., LTD. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Niuhang Electronics Technology Co., LTD. does not assume any and all implied warranties,including warranties of fitness for particular purpose,non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation.Customers are responsible in comprehending the suitable use in particular applications.Niuhang Electronics Technology Co., LTD.makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining,such as medical instruments,transportation equipment,aerospae machinery et cetera.Customers usin or selling these products for use in such applications do so at their own rish and agree to fully indemnify Niuhang Electronics Technology Co., LTD.for any damages resulting resulting from such improper use or sale.
- When the appearance of the product and chip size does not change, in order to product the customer. quality, change the internal structure and the production process Niuhang can not notify

NGT15N65D

N-Channel Enhancement Type IGBT With FRD



Specification Revision History

Rev.	Date	Changed Items	Pre-Changed Content	Changed Content
A/1	2025-10-20	First Issue		
Blank Below				